

08/14/00
jc901 U.S. PTO

jc901 U.S. PTO
09/638743
08/14/00

THE COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of:
Inventor: Geoffrey S. Ratte
For: FISHING LINE CLAMP
Enclosed are:

- ☒ 8 sheets of drawing.
- ☒ An assignment of the invention to Water Gremlin Company
- ☐ A certified copy of a _____ application.
- ☐ An associate power of attorney.
- ☒ A verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27.
- ☐ PTO 1449

The filing fee has been calculated as shown below:

BASIC FEE				\$345.00
TOTAL CLAIMS	- 20 =	0	X 10=	0
INDEPENDENT CLAIMS	- 3 =	0	X 30=	0
TOTAL				\$345.00

☐ Please charge my Deposit Account No. 10-0210 in the amount of \$ _____. A duplicate copy of this sheet is enclosed.

☒ A check in the amount of \$345.00 to cover the filing fee is enclosed.

☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 10-0210 . A duplicate copy of this sheet is enclosed.

☒ Any additional filing fees required under 37 CFR 1.16.

☐ Any patent application processing fees under 37 CFR 1.17.

☒ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 10-0210 . A duplicate copy of this sheet is enclosed.


☒ Any patent application processing fees under 37 CFR 1.17.

☐ The issue fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).

☒ Any filing fees under 37 CFR 1.16 for presentation of extra claims.

JACOBSON AND JOHNSON

By



Carl L. Johnson, Reg. No. 24,273
Attorneys for Applicant
Jacobson and Johnson
Suite 285
One West Water Street
St. Paul, Minnesota 55107-2080
Telephone: 651- 222-3775

Express Mail EK978901497US
Applicant or Patentee: Geoffrey S. Ratte

Attorney file: 5458/5012cp2

Serial or Patent No. _____
Filed or Issued: _____
For: FISHING LINE CLAMP

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9 (f) and 1.27 (c)) - SMALL BUSINESS CONCERN**

I hereby declare that I am

☐ the Owner of the small business concern identified below:
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF CONCERN Water Gremlin Company
ADDRESS OF CONCERN 1610 Whitaker Avenue, White Bear Lake, MN 55110

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled FISHING LINE CLAMP by inventor(s) Geoffrey S. Ratte described in

☒ the specification filed herewith.
☐ application serial no. _____ filed _____
☐ patent no. _____ issued _____

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who could not qualify as a small business concern under 37 CFR 1.9(d) or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(c). *NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

NAME Robert M. Ratte
ADDRESS 1 Island Rd. North Oaks Minn. 55127
☒ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))
I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that those statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

NAME OF PERSON SIGNING Robert Ratte
TITLE OF PERSON OTHER THAN OWNER: PRESIDENT
ADDRESS OF PERSON SIGNING 1610 Whitaker Avenue, White Bear Lake, MN 55110

SIGNATURE Robert M. Ratte DATE 8-14-2000

004780" E478E960

08/14/00
Jc907 U.S. PTO

8-15-00

A

JACOBSON AND JOHNSON

ATTORNEYS AT LAW
PATENT, TRADEMARK AND COPYRIGHT
SUITE 285
ONE WEST WATER STREET
ST. PAUL, MINNESOTA 55107-2033
TELEPHONE (651) 222-3775
FAX (651) 222-3776

Honorable Commissioner of Patents and Trademarks
Washington, D. C. 20231

SUBJECT: Applicant: Geoffrey S. Ratte
For: FISHING LINE CLAMP

Sir:

The enclosed subject application with 8 sheets of drawings and a check in the amount of \$345.00 is being sent by Express Mail No. EK978901497US. Under the provisions of 1.10 and 1.53, the applicant request the application be given the filing date of August 14, 2000.

Applicant's attorney, Carl L. Johnson, certifies that the application is being deposited with the United States Postal Service by Express Mail in an envelope addressed to: Commissioner of Patents and Trademarks, Washington, D.C. 20231 on August 14, 2000.

August 14, 2000
Date

Carl L. Johnson
Carl L. Johnson

Yours very truly,

JACOBSON AND JOHNSON

By Carl L. Johnson
Carl L. Johnson, Reg. No. 24,273
Attorneys for Applicant
Jacobson and Johnson
Suite 285
One West Water Street
St. Paul, Minnesota 55107-2080
Telephone: 651- 222-3775

0963342-081400

SPECIFICATION

TO WHOM IT MAY CONCERN

BE IT KNOWN, That I Geoffrey S. Ratte, a citizen of the United States, residing in Metairie, Jefferson County, State of Louisiana, have invented new and useful improvements in FISHING LINE CLAMP of which the following is a specification.

004780" 57489960

FIELD OF THE INVENTION

This invention relates generally to clamps and, more specifically, to a clamp sinker for holding a slideable worm weight or itself in a fixed position on a fishing line while inhibiting twisting action on the fishing line.

5

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation in part of my U.S. patent application 08/867/950 filed 6/30/97 which is a continuation in part of my U.S. patent application 08/651,053 filed 5/21/96 titled FISHING LINE CLAMP.

10

BACKGROUND OF THE INVENTION

The concept of worm weights and fishing rigs that use soft plastic worms is well known in the art. One of the more well known rigs is the Texas rig which uses a plastic worm, a slip sinker, called a worm weight, and a hook. The hook is extended through the end of the plastic worm with the pointed end of the hook embedded in the plastic worm to make the worm rig less prone to snagging. The worm weight, which is centrally located on the line has a bullet like shape with a central opening and fits around the line with sufficient clearance so the sinker is free to slide up and down the line. However, when fishing in weeds the sliding worm weight can cause problems as the worm weight tends to get hung up in the weeds. In order to prevent the worm weight from sliding a clamp is used to hold the worm weight in position on the line. A prior art method of clamping the worm weight in position is accomplished by forcing a toothpick into the opening in the worm weight which jams the line against the interior passage in the worm weight thus preventing the worm weight from slipping on the line. The present invention comprises an improved clamp sinker to hold the worm weight in position without having to use a toothpick to jam the line against the worm weight or to hold itself in centered position on a fishing line. The present invention provides a line clamp sinker that can be attached to the line in front of the

worm weight and because of the streamline shape on the exterior surface of the clamp the clamp coacts with the sinker shape to form a fishing rig that can be pulled through the water and weeds with a minimum of snagging or line twisting. As an alternate use as a clamp sinker the clamp sinker can be secured to the line to hold itself in position or another fishing

5 item in position while providing sinker action.

BRIEF DESCRIPTION OF THE PRIOR ART

U.S. patent 1,618,100 shows a fishing sinker with crevices for looping the fishing line around the sinker.

1 0

U.S. patent 2,735,652 shows a tear shaped fishing sinker where the line is looped around the sinker.

U.S. patent 2,741,067 shows a snap on sinker with a ring to hold the halves of the sinker in position on the fishing line.

1 5

U.S. patent 3,701,212 shows a salt water sinker with crimpable arms that prevents removal of the sinker from a line.

2 0

U.S. patent 4,145,833 shows a fishing sinker with two halves that can be clamped on a fishing line to hold a line and bait under water.

U.S. patent 4,279,092 shows a fishing weight having an insert therein for engaging a fishing line.

2 5

U.S. patent 4,459,775 shows a weedless sinker having nubs on each end of the sinker to fold over the line.

U.S. patent 4,837,966 shows a cam action fishing sinker device.

U.S. patent 4,891,903 shows a sliding or fixed fishing sinker where the line can be looped
5 on the sinker to prevent the sinker from sliding.

U.S. patent 4,944,107 shows a fixed and sliding spherical fishing sinker for attachment to
a fishing line by clamping the two halves to the fishing line.

1 0 U.S. patent 4,964,236 shows a fishing line sinker having a quick attachment device.

SUMMARY OF THE INVENTION

Briefly, the present invention comprises a streamline clamp sinker for attachment to a
fishing line in front of a worm weight or by itself with the clamp sinker presenting a
1 5 streamline shape to inhibit action that might twist the line as the line as the clamp sinker is
pulled through the water.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a prior art Texas rig with the worm weight being secured in position with a
2 0 toothpick;

Figure 2 shows the Texas rig of Figure 1 with the line clamp of the present invention
attached thereto to prevent the worm weight from sliding on the fishing line;

2 5 Figure 3 shows an enlarged view of the portion of Figure 2 outlined by dotted lines;

Figure 4 shows an end view of the clamp and worm weight of Figure 3;

Figure 5 shows a sectional view taken along lines 5-5 of Figure 3;

Figure 6 is perspective view of the clamp of Figure 2;

5

Figure 7 is a cross sectional view taken along lines 7-7 of Figure 3;

Figure 8 is cross sectional view of a first half of a line clamp showing a peripheral hinge;

1 0 Figure 9 is a cross sectional view of the other half of line clamp of Figure 8;

Figure 10 is an assembled view of the line clamp of Figure 8 and Figure 9;

1 5 Figure 11 is a perspective view of an alternate embodiment of a line clamp sinker in an open condition;

Figure 12 is perspective view of a further alternate embodiment of a line clamp sinker in a closed condition;

2 0 Figure 13 is a cross sectional view of the line clamp sinker of Figure 12;

Figure 14 is a cross sectional view taken along lines 14-14 of Figure 12;

Figure 15 is a cross sectional view taken along lines 15-15 of Figure 12; and

2 5

Figure 16 is a cross sectional view taken along lines 16-16 of Figure 12;

DESCRIPTION OF THE PREFERRED EMBODIMENT

Figure 1 shows a Texas rig 10 for fishing with plastic worms or the like. The Texas rig includes a flexible plastic worm 11 having a head 13 and a tail 12. A hook 15 connects to one end of line 14 and extends through head 13 with the pointed end of hook 15 embedded

5 in the worm to minimize snagging of the rig as it is pulled through the water. In order to maintain the plastic worm at the proper fishing depth a lead weight commonly referred to as a worm weight 16 is mounted on line 14 immediately in front of head 13. Worm weight 13 generally comprises a bullet shaped article with a line hole extending through the weight.

Figure 1 shows the prior art clamping device for securing the worm weight to line 13 comprising a breakable wood toothpick 17 which has had one end jammed into the opening

1 0 of the worm weight that carries the fishing line. Once the toothpick is jammed in the opening the toothpick is broken off so that only a small portion of the toothpick protrudes from the worm weight.

Figure 2 shows the Texas rig 10 with line clamp 20 of the present invention located in front

1 5 of worm weight 16.

Figure 3 shows line clamp or clamp sinker 20 and the front portion of the Texas rig in greater detail. Line clamp 20 is movable between an open condition (Figure 6) and a closed

2 0 condition, as shown in Figure 2, for preventing worm weight 16 from sliding along fishing line 14. Line clamp 20 comprises a body of bendable material for circumferentially squeezing a fishing line with the line clamp having a first leading end 21 and a second larger end with the first end 21 of line clamp 20 being smaller in cross sectional area than the second end 22 when the line clamp is attached to a fishing line. Clamp 20 is

2 5 characterized by being smaller than the worm weight and having an exterior surface with the exterior surface of the body smoothly converging from first end 21 to the second end 22 to form a streamline shape that inhibits twisting or propeller action of the clamp as the

rig is pulled through the water. By inhibiting propeller action by the line clamp one inhibits line twisting which can lead to snarling of the line in the reel. The streamline shape of line clamp 20 is compatible with a streamline shape of a worm weight 16 so that when the line clamp 20 is positioned in front of worm weight 16 it not only acts as a stop for a worm weight 16 but the streamline shape of the body of line clamp 20 cooperates with the streamline shape of the worm weight 16 to produce a fishing rig that minimizes snagging as the rig is pulled through weeds.

Figure 6 shows line clamp 20 with bendable jaws 26 and 27 in the open condition. Line clamp 20 includes a first line gripping surface 23 extending to the geometric center of clamp 20 as defined by surface 28. Gripping surface 23 extend from the first end 21 to the second end 22 with second end 22 having a flat surface for allowing the worm weight to adopt a central position thereon. That is surface 27 by being symmetrical does not force the worm weight to follow there behind in an unusual angle. Line gripping surface 23 includes at least one recess surface and line gripping surface 24 includes a raised surface that forms mating engagement with line gripping surface 24 to circumferentially grasp and lock a line therein by providing a nonlinear path through the line clamp. That is, when the line gripping surface 23 and line gripping surfaces 24 are in the closed condition they coact to grasp a fishing line located therein and prevent the slippage of the fishing line therein. As the jaws extend to the geometric center of the clamp a line placed in the bottom 28 of the clamp 20 will be positioned in the center of the clamp and will minimize the tendency of the clamp to act like a propeller as the clamp 20 is pulled through the water as well as minimizing snagging in the weeds. Jaws 23 and 24 are characterized by being asymmetrical in that the hinge region formed as the jaws 23 and 24 interact and vary from a first thickness to a second larger thickness.

Figure 4 shows an end view of the worm weight and line with line clamp 20 located thereon. In this view one notes that the line clamp is considerably smaller than the worm weight and has diverging sides that diverge outward in the same manner as the sides of worm weight 16 to produce a rig that can be pulled through the weeds with a minimum of snagging.

Figure 7 shows a cross sectional view taken along lines 7-7 of Figure 3 to illustrate the worm weight 16 is a solid piece of material with a central opening therein for a fishing line. It should be kept in mind that the worm weight is placed on the line for weight and although the line clamp 20 has an incidental weight it is the central clamping action of the line clamp that performs the line holding function. Line Clamp 20 includes an outer truncated cone shape with a neutral stop surface 22 to prevent sliding of the worm weight along the fishing line. Surface 20 is a neutral stop surface as surface 22 does not force the worm weight askew of the fishing line by a clamp that would provide a guide surface that directs either of the clamp or the worm weight to a path which is not parallel to the fishing line.

Figure 5 is a cross sectional view taken along lines 5-5 of Figure 3 to illustrate that the surfaces 23 and 24 are in mating engagement with each other and that line 14 is located in the center of clamp 20 as indicated by the equal dimensions "r" extending radially outward from fishing line 14 which is located in the center of clamp 20.

As can be seen from the drawings, line clamp 20 is made from a nonresilient material which can be bent around the line, preferably by finger pressure. Suitable materials are plastics and certain metals. If the worm weight is made of lead a suitable material for making the line clamp, could be lead; however, the line clamp like the hook is not on the line to provide weight but is attached to the line to grasp the line and prevent the worm

weight from sliding while creating a generally streamline shaped stop that is not prone to acting like a propeller. Line clamp 20 when used in conjunction with a worm weight should be made sufficiently small so that the weight of the line clamp 20 is insufficient to act or perform as a weight for the fishing rig.

5

Figure 8 shows a sectional view of one half of a tension adjusted line clamp or sinker stopper 30 and Figure 9 shows a sectional view of the other half of a tension adjusted line clamp or sinker stopper 30 with an integral peripheral hinge 33 (shown in section) for connecting the two halves together. One half of sectioned sinker stopper is identified by

1 0 numeral 37 and is shown in Figure 8 and the other half of sectioned sinker stopper is identified by reference numeral 39 and is shown in Figure 9. In order to reveal the interior of sinker stopper 30 the sinker stopper has been sectioned axially and each of the halves 37 and 39 are shown in a plane view with the common connecting region 33, which forms a tension adjusted peripheral hinge 33, having an area A_0 and line centering surfaces 34 and
1 5 34a located on opposite ends of hinge 33. The use of a controlled connecting area A_0 allows one to preset the tension force necessary to open and close the two halves of the sinker stopper 30 and still maintain the streamline exterior that prevents twisting. That is, with a larger area A_0 the sinker stopper is more difficult to open and close and with a smaller area A_0 the sinker stopper is less difficult to open and close. Consequently, one can
2 0 form a sinker stopper of various sizes that are suitable for squeezing around a fishing line without undue finger pressure. In addition the use of line centering surfaces 34 and 34a located on peripheral hinge 33 maintain the line 35 in a centered condition within sinker stopper 30.

2 5 Figure 8 shows that a protrusion 31 extends from the hinge area 33 to the opposite edge of sinker stopper and Figure 9 shows that a mating recess 38 extends from hinge 33 to the opposite side of sinker half 39.

Figure 10 shows a top view of sinker stopper 30 in the unsectioned condition with protrusion 31 on sinker half 37 engaging recess 38 on sinker half 39. Located on the top half of sinker half 37 is a first relief which I refer to as a thumbnail recess 61 and located on the bottom half of sinker 37 is a second relief which I also refer to as a thumbnail recess 60 that allow a user to quickly pry open a closed sinker to remove a line without the aid of any special tools by inserting his or her thumbnail or fingernail therein. The thumbnail recess 60 and 61 comprises an elongated peripheral relief that extends radially inward sufficiently far for a user to insert his or her fingernail into the thumbnail recess. As one thumbnail recess is located on each of the halves it permits a user to pry apart the sinker 37 when the sinker is in a closed condition. That is, a first thumbnail is inserted in recess 61 which allows user to bear against lower half of sinker 37 and a second thumbnail inserted in recess 60 allows a user to bear against upper half of sinker 37 to open sinker 37.

In the embodiment 30 the sinker stopper provides line centering capabilities through line centering surfaces 34 and 34a which are spaced a distance "x" from a center line 35. That is the line centering surfaces can be spaced a distance generally equal to half the thickness of the fishing line in order to ensure that the sinker stopper is centered on the line. With use of small diameter lines the line centering surfaces 34 and 34a can be placed on the geometric center defined by central axis 32 without affecting the balance of the sinker stopper 30.

A further feature of the invention is that the peripheral hinge with surface stops 34 and 34a can be formed by forcing a knife-like blade into the central portion of the line clamp 30 sufficiently far so as to form the peripheral hinge 33.

Figure 11 shows an alternate embodiment of line clamp sinker 40 with bendable jaws 45 and 46 in the open condition. Line clamp 40 includes a first smoothly curved, undulating

gripping surface 43 extending to the center of clamp 40 as defined by surface junction line 47. A first curved gripping a symmetrical surface 43 extends from the first end 41 of line clamp 40 to the second end 42 of line clamp 40. Second end 42 of clamp 40 has a flat surface 46 for allowing a worm weight or the like to adopt a central position thereon.

5

Curved gripping surface 43 includes at least one smoothly curved surface contouring protrusion and a second curved, undulating asymmetrical gripping surface 44 includes at least one surface contouring recess that forms mating engagement with line gripping surface 43 to circumferentially grasp and lock a line therebetween by providing a curving,

10

undulating path through line clamp 40. That is, when first curved gripping surface 43 and second curved gripping surface 44 are in the closed condition they coact to grasp the

fishing line located therein and prevent the slippage of the fishing line therein by frictional engagement which is aided by the longer curved surfaces since the length of line in contact with the sinker is longer than if the surface were straight. In addition, the curved surfaces

15

ensure that the line is not damaged by the jaws. As the jaws extend to the geometric center of the clamp a line placed in the bottom 47 of clamp 40 is positioned in the center of the clamp minimizes the tendency of the clamp to act like a propeller as clamp 40 is pulled through the water as well as minimizing snagging in the weeds. Jaws 45 and 46, by having a curved gripping surface, will alleviate undue stress as a result of the grip that clamp 40

20

has on the line when clamp 40 is in the closed position.

Located at the peripheral edge of sinker 40 is a first thumbnail recess 63 and a second thumb nail recess 62 which extend inward sufficiently far for a user to insert his or her fingernail or thumbnail therein. Typically, the thumbnail recess need extend in a 1/16 of an inch. Once inserted the user can quickly pry open the sinker. In the embodiment shown the thumbnail recess have a pie shape appearance with the edges of the relief smoothly blending into the sinker to eliminate any sharp edges.

25

Figure 12 shows a line clamp 50 of a different embodiment than the line clamp 40 embodiment shown in Figure 11. Line clamp 50 is shown with jaws 55 and 56 in a closed position gripping line 48 to form a cone-shaped structure. Line 48 is being grasped by line clamp 50 and is shown exiting from first end 51 and second end 52 of line clamp 50. The mating engagement between first curved line gripping surface 53 and second curved line gripping surface 54 forms a curving path through line clamp 50 for gripping and locking line 48 to prevent line 48 from slipping off of line clamp 50.

Figure 13 is cross sectional view of the top of line clamp 50 showing an integral peripheral hinge 59 connecting the two jaws together. Peripheral hinge 59 has a first line centering surface 57 located at the first end 51 of line clamp 50 and a second line centering surface 58 located on the second end 52 of line clamp 50 for maintaining line 48 in a centered condition within line clamp 50. Located between first line centering surface 57 and second line centering surface 58 is a recess 60. The area of recess 60 is indirectly proportional to the area of peripheral hinge 59. If the area of recess 60 increases, the area of peripheral hinge 59 will decrease; vice versa, if the area of recess 60 decreases, the area of peripheral hinge 59 will increase. The area of peripheral hinge 59 controls the tension force necessary to open and close the jaws of line clamp 50 in that line clamp 50 is more difficult to open and close than with a larger peripheral area than a smaller peripheral area. In the embodiment shown the mating surfaces extend slightly past the center line so that line 48 can be engaged along the entire length of the sinker clamp.

Figure 14 is a cross sectional view of Figure 12 taken along the lines 14-14 to illustrate that the first end 51 of clamp 50 is composed of a solid core with peripheral hinge 59 having a width of L_1 . Also locate at the first end 51 of line clamp 50 is first line centering surface 57 for maintaining the line in a centered condition at first end 51 of clamp 50.

Figure 15 is a cross sectional view of Figure 12 taken along the lines 15-15 showing the mid section of line clamp 50, recess 60, and peripheral hinge 59 having a width of L_2 . The existence of recess 60 allows line clamp 50 to require less tension force necessary to open and close the jaws of line clamp 50 than if recess 60 did not exist in line clamp 50. The area of recess 60 is indirectly proportional to the area of peripheral hinge 59. Figure 15 illustrates the geometric center 59 is located between the faces of the sinker so that if a line extends through the geometric center the line can be grasped along the entire length of line located between the two ends of the sinker.

10

Figure 16 is a cross sectional view of Figure 12 taken along the lines 16-16 to illustrate that second end 52 of clamp 50 is also composed of a solid core with peripheral hinge 59 having a width of L_3 . Also locate at second end 52 of line clamp 50 is second line centering surface 58 for maintaining the line in a centered condition at second end 52 of clamp 50.

15

I claim:

1. A clamp sinker movable between an open and closed condition comprising:

a body composed of a bendable material, said body being cone shape and having a neutral surface, said body having a first end and a second end with said first end of said body being smaller than the second end of said body with said body having a smoothly converging exterior surface from said first end to said second end to form a streamline shape that inhibits snagging and propeller action as the body is pulled through a fluid;

a first curved gripping surface on said body, said first curved gripping surface undulating through said body to provide a surface free of angled corners to thereby inhibit line damping, said first curved gripping surface extending from said first end to said second end, said first curved gripping surface having at least one surface contouring protrusion, said first curved gripping surface having a portion extending proximate a geometric center of said line clamp; and

a second curved gripping surface on said body said second curved gripping surface undulating through said body to provide a surface free of angled corners o thereby inhibit line damping, said second curved gripping surface extending from said first end to said second end with said second curved gripping surface including a surface contouring recess mateable with said protrusion to produce a nonlinear path through said resilient body so that when said second curved gripping surface and said first curved gripping surface coact to grasp a line located therein to prevent the slippage of the line therein as the line is squeezed and held therebetween by bending said line clamp around the line.

2. The line clamp sinker of claim 1 including an integral peripheral hinge connecting the two jaws together, said peripheral hinge having a first line centering surface located at the first end of said line clamp and a second line centering surface located on the second of said

line clamp, said line centering surface for maintaining said line in a centered condition within line clamp.

3. The line clamp sinker of claim 2 including a recess located between said first line

5 centering surface and second line centering surface , said recess allowing said line clamp to require less tension force necessary to open and close the jaws of said line clamp than if said recess did not exist.

10 4. The line clamp of claim 1 wherein the body is a single continuous integral member with each of the line gripping surfaces asymmetrical but mateable with each other.

5. The line clamp of claim 1 wherein the body is an alloy of bismuth.

15 6. The line clamp of claim 2 wherein the body is finger bendable.

7. The line clamp of claim 1 wherein the body is a continuous integral member.

20 8. The line clamp of claim 1 wherein the line clamp has an exterior diverging surface and a set of jaws that extend the entire length of the line clamp.

9. The line clamp of claim 1 wherein the line clamp is one piece and includes two asymmetrical jaws extending to a geometric center of said line clamp with said jaws are movable between an open condition and a closed condition by pivoting the jaws.

25 10. The line clamp of claim 1 including a first relief on a top half of the sinker and a second relief on the bottom half of the sinker to permit a user to insert to insert a fingernail or thumbnail thereon to pry apart the sinker if the sinker is in a closed condition.

11. A clamp sinker movable between an open and closed condition comprising:

a body composed of bendable material, said body being cone shape and having a neutral surface, said body having a first end and a second end with said first end of said body being smaller than the second end of said body with said body having a smoothly converging exterior surface from said first end to said second end to form a streamline shape that inhibits snagging and propeller action as the body is pulled through a fluid;

a first line gripping surface on a first end of said body, said first line gripping surface

a second line gripping surface on the first end of said body for mating engagement with said first line gripping surface;

a third line gripping surface on said second end of said body, said third line gripping surface spaced from said first line gripping surface; and

a fourth line gripping surface on the third end of said body for mating engagement with said third line gripping surface with said first line gripping surface and said second line gripping surface holding a line in a centered condition on the first end of the clamp sinker and the third line gripping surface and the fourth line gripping surface holding the line in a centered condition on the second end of said body.

ABSTRACT OF THE DISCLOSURE

A fishing line clamp sinker with a tension adjusted hinge having line centering surfaces
5 including a streamline clamp for attachment to a fishing line in front of a worm weight or
the like to prevent the worm weight from sliding along the fishing line with the clamp
sinker present a streamline shape to inhibit action that might twist the line as the line and
sinker are pulled through the water.

10

004T80" E428E960

PRIOR ART




FIG. 1




FIG. 2




FIG. 3




FIG. 6




FIG. 4




FIG. 7






FIG. 5






Figure 11





Figure 12



40

Figure 13

48

41

54

53

56




Fig. 14




Fig. 15




Fig. 16

